(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 5 January 2006 (05.01.2006)

PCT

(10) International Publication Number WO 2006/001622 A1

(51) International Patent Classification7:

F16D 3/50

(21) International Application Number:

PCT/KR2005/001898

(22) International Filing Date: 18 June 2005 (18.06.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 10-2004-0048062

25 June 2004 (25.06.2004) KR

- (71) Applicant (for all designated States except US): MONASPUMP CO., LTD. [KR/KR]; 3-MA-815, Sihwa Industrial Complex, Jeongwang-dong, Siheung-city, Kyungki-do 429-935 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): LEE, Man-Soo [KR/KR]; 3-305 Sindonga Apt. 988-1 Bangbae3-dong, Secho-gu, Seoul 137-758 (KR).
- (74) Agent: Y.P.LEE, MOCK & PARTNERS; The Cheonghwa Building, 1571-18, Seocho-dong, Seocho-gu, Seoul 137-874 (KR).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, co, CR, cu, cz, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KQ, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, X, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLEXIBLE TRANSMISSION SHAFT



(57) Abstract: Provided is a flexible transmission shaft. The flexible transmission shaft for transmitting a torque from a drive source to a driven load, the flexible transmission shaft includes a pipe-shaped shaft, which has one or more slits extending in a circumferential direction of the shaft, each of the slits having two opposed surfaces that are isolated from each other by the slit, a plurality of protrusions protruding from one of the opposed surfaces, and a plurality of recessions formed in the other one of the opposed surfaces to receive and support the protrusions therein. Since the flexible transmission shaft can be bent or curved within a given angle, it can be substituted for a flexible coupling, a universal joint, or a bevel gear. In addition, the flexible transmission shaft does not require additional mechanical elements to be connected to a shaft, and has a simple structure, light weight, and high torque transmission capability.